

Belt grinders - model TAS - HM TAS 75X

Item Number: 00103067

HM TAS 75X and 150X are efficient quality belt grinder with built-in double exhaust system

TAS 75X and 150X are manufactured in accordance with the strictest environmental- and health and safety regulations.

Standard machines are equipped with built-in double dust extraction, motor brake, adjustable top work support, eye shield, thermal overload no volt release starter and emergency stop. The machines are suitable for grinding all metals, they are CE-approved and have a low level of noise.

Standard features:

- Danish design and top quality.
- Dust extraction
- Powerful motors
- Thermal Overload No Volt Release starter
- Separate emergency stop
- Electronic Motor-brake
- Adjustable top work support
- Eye protection
- Working height can be set to the most optimum position
- Unique design for clean, quick and safe grinding
- Self-adjusting belt tensioner

Optional accessories

- Centerless grinding attachments (dry or wet)
- Pipe notching attachment



Product Specifications

With exhaust	✓
Belt speed (m/sec)	32
Exhaust (m ³ /h)	630
Grinding belt (mm)	75x2000
Grinding table (mm)	75x605
Machine height (mm)	1000
Machine length (mm)	1025

Machine width (mm)	500
Motor (HP)	4,1
Net weight (kg)	90
Voltage	3x400/440V-50/60 Hz
Wheel size, Contact wheel (ø mm)	200x75x20
Wheel size, Drive wheel (ø mm)	200x75x24
Without extraction	1