

Belt grinders - model TAS - HM TAS 150

Item Number: 00103217

HM TAS 75 and 150 are efficient quality belt grinder

TAS 75 and 150 are manufactured in accordance with the strictest environmental- and health and safety regulations.

Standard machines are equipped with motor brake, adjustable top work support, eye shield, thermal overload no volt release starter and emergency stop. The machines are suitable for grinding all metals, they are CE-approved and have a low level of noise.

Standard features:

- Danish design and top quality.
- Powerful motors
- Thermal Overload No Volt Release starter
- Separate emergency stop
- Electronic Motor-brake
- Adjustable top work support
- Eye protection
- Working height can be set to the most optimum position
- Unique design for clean, quick and safe grinding
- Self-adjusting belt tensioner

Optional accessories

- Dust extraction
- Centerless grinding attachments (dry or wet)
- Pipe notching attachment



Product Specifications

With exhaust	✓
Belt speed (m/sec)	32
Grinding belt (mm)	150x2000
Grinding table (mm)	150x605
Machine height (mm)	1000
Machine length (mm)	1025
Machine width (mm)	600
Motor (HP)	4,8
Net weight (kg)	100

Voltage	3x400/440V-50/60 Hz
Wheel size, Contact wheel (ø mm)	200x150x20
Wheel size, Drive wheel (ø mm)	200x150x28